



T H E

# O H A U S T R O O P E R S E R I E S

*economical compact industrial bench scales*



The Trooper's design is optimised for economical weighing in approved or non-approved applications. A concave stainless-steel weighing pan and ABS housing provide protection for light industrial conditions. Simple menu operation and easy-to-read backlit LCD display make the Trooper an affordable weighing solution.

- Up to 1 part in 7,500 maximum resolution or 3000e class III, EC type-approved
- Durable ABS housing with stainless steel weighing platforms
- RS232 interface standard
- Weigh in lb, kg, g or oz
- AC power or up to 100 hours battery operation



# Trooper

## Economical Compact Industrial Bench Scales



Standard Models	TR3RS	TR6RS	TR15RS	TR30RS
Capacity	3 kg	6 kg	15 kg	30 kg
Factory preset readability Non approved	0.5 g	1 g	2 g	5 g
Approved preset readability (e=d)	1g	2g	5g	10g
Linearity	±0.5 g	±1.0 g	±2.0 g	±5.0 g

### General Specifications

Platform Size (w x d)	34 x 23 cm
Scale Dimensions (w x d x h)	34.3 x 36.8 x 11.4 cm
Shipping Dimensions (w x d x h)	42.2 x 42.2 x 21.6 cm
Weight	3.9 kg
Resolution Maximum	Up to 1:7,500
Stabilization Time	1 – 4 seconds depending upon filter selection
Keyboard	4 function membrane switches
Weighing Units	lb, kg, g, oz (Changing from kg to lb only for the countries where the use of lb is allowed)
Display	Backlit LCD, 25.4 mm
Power	AC Adapter or 6 C-type Batteries
Typical Battery Life	Up to 100 hours
Span Calibration	20% to 100% of capacity
Linearity Calibration (3-point calibration)	0% 50% 100%
Auto Zero Tracking	Off, 0.5, 1 or 3 divisions
Construction	Stainless steel weighing pan, ABS plastic housing
Protection	IP43
Operating Temperature	-10 °C to 45 °C
Storage Temperature	-20 °C to 60 °C

All Trooper models meet the requirements of Approval Agencies: UL, FCC, CSA, CE.  
EC Type-approval certificate: T6028

### Standard Features

RS232 bi-directional interface, backlit LCD display, Net/Gross/Tare function, auto-off timer, low battery warning, adjustable averaging and stability levels, retain zero data, auto-zero tracking, leveling feet, leveling bubble.

### Optional Accessories

Carrying case, RS232 interface cables.

**Ohaus UK Ltd.**  
64 Boston Road  
Beaumont Leys  
Leicester LE4 1AW  
ENGLAND  
Tel.: +44 116 234 5075  
Fax: +44 116 234 6706  
e-mail: [uksales@ohaus.com](mailto:uksales@ohaus.com)

**Ohaus Europe & MEA**  
Heuwinkelstrasse  
CH-8606 Nänikon  
Switzerland  
Tel.: +41-1-944 33 66  
Fax: +41-1-944 32 30  
e-mail: [EuropeSales@Ohaus.com](mailto:EuropeSales@Ohaus.com)

**Ohaus Corporation**  
\* 19 Chapin Road  
Pine Brook, NJ 07058 USA  
Tel.: +1-973-377-9000  
Fax: +1-973-593-0359  
e-mail: [OhausHQ@Ohaus.com](mailto:OhausHQ@Ohaus.com)

*With offices in Mexico, Switzerland, England, Germany, France, Spain, Italy, Poland, Russia, Japan, Korea and China*

\* **ISO 9001**  
Registered Quality Management System

[www.ohaus.com](http://www.ohaus.com)